

PM 55_in spot



Luminary

Luminária

- L70 > 50000h
- MacAdam 3

LED/Optic Òptica

- COB LUMINUS
- Reflector

Voltage Voltaje

- 220-240VAC

Dimming Regulación

- ON-OFF
- PH-CUT
- 1-10V
- PUSH ONLY
- DALI-2

Protection Protección

- IP20

Accessories Accesorios

- Honeycomb
Panal de abeja
- Frosted glass
Cristal glaseado

Basic finishes

Acabados básicos

- Black
- White

Special finishes

Acabados especiales

NCS

- Oliva - S 7010-G30Y
- Ocre - S 5040-Y70R
- Terracota - S 3050-Y60R
- Mocha - S 5010-Y10R
- Sand - S 2005-Y50R

Metallic Metálico

- Gun Metal
- Bronze
- Brushed Copper
- Old Silver
- Cava

Downloads Descargas



Cod.	W	Beam angle	CRI	K	Lm	Efficiencie
2204.92700920.x	10,3W	20°	90	2700K	683Lm	67Lm/W
2204.92700940.x	10,3W	40°	90	2700K	683Lm	67Lm/W
2204.92700960.x	10,3W	60°	90	2700K	683Lm	67Lm/W
2204.93000920.x	10,3W	20°	90	3000K	779Lm	76Lm/W
2204.93000940.x	10,3W	40°	90	3000K	779Lm	76Lm/W
2204.93000960.x	10,3W	60°	90	3000K	779Lm	76Lm/W
2204.94000920.x	10,3W	20°	90	4000K	870Lm	85Lm/W
2204.94000940.x	10,3W	40°	90	4000K	870Lm	85Lm/W
2204.94000960.x	10,3W	60°	90	4000K	870Lm	85Lm/W
2204.92701225.x	13,6W	25°	90	2700K	1080Lm	80Lm/W
2204.92701243.x	13,6W	43°	90	2700K	1080Lm	80Lm/W
2204.92701260.x	13,6W	60°	90	2700K	1080Lm	80Lm/W
2204.93001225.x	13,6W	25°	90	3000K	1217Lm	90Lm/W
2204.93001243.x	13,6W	43°	90	3000K	1217Lm	90Lm/W
2204.93001260.x	13,6W	60°	90	3000K	1217Lm	90Lm/W
2204.94001225.x	13,6W	25°	90	4000K	1318Lm	97Lm/W
2204.94001243.x	13,6W	43°	90	4000K	1318Lm	97Lm/W
2204.94001260.x	13,6W	60°	90	4000K	1318Lm	97Lm/W

